




## Noctambule Suspension 2 Low Cylinder Bowl

■ F0273000 - Black

Designed by Konstantin Grcic

Hanging lamps consisting of interconnecting glass modules reaching a length of 3,2 mt. (126.77") with 4 mt. (157.48") suspended power cable. Cylindrical and semi-spherical transparent blown glass structure, suspended die cast aluminium ring connector, hydroformed steel internal lateral arm and injection moulded optical opal silicone outer ring diffusers. The power supply unit within the ceiling rose can be used as a dimmer to adjust the light intensity by 10% to 100% in either direction by means of the 0-10/1-10V, PUSH, DALI control.



### Main specifications

<b>Mounting</b>	Suspension	<b>Lamp holder</b>	LED Module, COB LED
<b>Environment</b>	Indoor dry location	<b>Dimmable</b>	Yes
<b>Light source type</b>	LED	<b>Autoprotected Lamp</b>	No
<b>Light source replaceable</b>	Replaceable (LED only) light source by a professional	<b>Source Power (W)</b>	45
		<b>System Flux (lm)</b>	1007
<b>LED type</b>	LED Module		

### Optical

<b>Lighting Type</b>	Total
<b>Lighting distribution</b>	Symmetric
<b>CCT (K)</b>	2700
<b>CRI&gt;</b>	90
<b>Cold Beam Lighting</b>	No
<b>Extreme Cut off</b>	No

### Electrical

<b>Insulation class</b>	I	<b>Dimmable type</b>	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
<b>Frequency (Hz)</b>	50/60	<b>Batteries Inside</b>	No
<b>Main Voltage (Vac)</b>	120-277	<b>Dimming Interface</b>	Remote Dimmable (Dimmer Not Included)
<b>Driver</b>	Integrated	<b>Power supply replaceable</b>	Replaceable control gear by a professional
<b>Dimmable</b>	Yes	<b>Cord length (mm)</b>	4000
<b>Charging Min Time</b>	No		

### Physical

<b>Colour</b>	Black
<b>Net weight (kg)</b>	14.2
<b>Gross weight (kg)</b>	31.31
<b>IP</b>	20
<b>IP external</b>	20

